

# CERTIFICATE OF CONFORMITY

Issued to: GoodWe Technologies Co., Ltd.  
No. 90 Zijin Rd., New District, Suzhou, 215011, China

For the product: Grid-Tied PV Inverter

Trade name: **GOODWE**

Type/Model: GW4000-SDT-30, GW5000-SDT-30, GW6000-SDT-30  
GW8000-SDT-30, GW10K-SDT-30, GW12K-SDT-30,  
GW15K-SDT-30, GW20K-SDT-30, GW25K-SDT-C30,  
GW30K-SDT-C30,

Ratings: See Annex

Manufactured by: GoodWe Technologies Co., Ltd.  
No. 90 Zijin Rd., New District, Suzhou, 215011, China

Requirements: IEC 61683:1999  
EN 50530:2010+A1:2013  
IEC 62891: 2020

This Test Certificate is granted on account of an examination by DEKRA, the results of which are laid down in a confidential file no. 6215774.50(A-B), 6215774.52

The examination has been carried out on one single specimen of the product. The certificate does not include an assessment of the minilecture's production. Conformity of his production with the specimen tested by DEKRA is not the responsibility of DEKRA.

This Test Certificate expires at the latest on 2030-02-17 or expires upon withdrawal of one of the above mentioned standards.

Shanghai, 2025-02-17

Number: 6215774.01COC

DEKRA Testing and Certification (Shanghai) Ltd.



Kreny Lin  
Certification Manager

© Integral publication of this certificate and adjoining reports is allowed

DEKRA Testing and Certification (Shanghai) Ltd.  
No.250, Jiangchangsan Road, Jing'an District, Shanghai, 200436 People's Republic of China  
T +86 21 6056 7600 F +86 21 6056 7555 [www.dekra-product-safety.com](http://www.dekra-product-safety.com)  
ESA-CER-F021 v4.1



PCA-141

Document no. : 6215774.01COC

## Ratings of product:

Operating temperature range: - 30°C to + 60°C

Protective class: I

Ingress protection rating: IP66

Power factor range (adjustable): 0.8 leading...0.8 lagging

### GW4000-SDT-30:

PV input: Max. 1100 Vdc, MPPT voltage range: 140-1000 Vdc, max: 2\*22 A, Isc PV: 2\*27.5 A

Output: 3L/N/PE or 3L/PE, 220/380 Vac, 230/400 Vac, 240/415 Vac, 50/60 Hz, max 6.7 A, max 4.4 kVA

### GW5000-SDT-30:

PV input: Max. 1100 Vdc, MPPT voltage range: 140-1000 Vdc, max: 2\*22 A, Isc PV: 2\*27.5 A

Output: 3L/N/PE or 3L/PE, 220/380 Vac, 230/400 Vac, 240/415 Vac, 50/60 Hz, max 8.4 A, max 5.5 kVA

### GW6000-SDT-30:

PV input: Max. 1100 Vdc, MPPT voltage range: 140-1000 Vdc, max: 2\*22 A, Isc PV: 2\*27.5 A

Output: 3L/N/PE or 3L/PE, 220/380 Vac, 230/400 Vac, 240/415 Vac, 50/60 Hz, max 10.0 A, max 6.6 kVA

### GW8000-SDT-30:

PV input: Max. 1100 Vdc, MPPT voltage range: 140-1000 Vdc, max: 2\*22 A, Isc PV: 2\*27.5 A

Output: 3L/N/PE or 3L/PE, 220/380 Vac, 230/400 Vac, 240/415 Vac, 50/60 Hz, max 13.4 A, max 8.8 kVA

### GW10K-SDT-30:

PV input: Max. 1100 Vdc, MPPT voltage range: 140-1000 Vdc, max: 2\*22 A, Isc PV: 2\*27.5 A

Output: 3L/N/PE or 3L/PE, 220/380 Vac, 230/400 Vac, 240/415 Vac, 50/60 Hz, max 16.7 A, max 11 kVA

### GW12K-SDT-30:

PV input: Max. 1100 Vdc, MPPT voltage range: 140-1000 Vdc, max: 2\*22 A, Isc PV: 2\*27.5 A

Output: 3L/N/PE or 3L/PE, 220/380 Vac, 230/400 Vac, 240/415 Vac, 50/60 Hz, max 20 A, max 13.2 kVA

### GW15K-SDT-30:

PV input: Max. 1100 Vdc, MPPT voltage range: 140-1000 Vdc, max: 2\*22 A, Isc PV: 2\*27.5 A

Output: 3L/N/PE or 3L/PE, 220/380 Vac, 230/400 Vac, 240/415 Vac, 50/60 Hz, max 25 A, max 16.5 kVA

### GW20K-SDT-30:

PV input: Max. 1100 Vdc, MPPT voltage range: 140-1000 Vdc, max: 32/22 A, Isc PV: 40/27.5 A

Output: 3L/N/PE or 3L/PE, 220/380 Vac, 230/400 Vac, 240/415 Vac, 50/60 Hz, max 33.3 A, max 22 kVA

### GW25K-SDT-C30:

PV input: Max. 1100 Vdc, MPPT voltage range: 140-1000 Vdc, max: 42/22 A, Isc PV: 52.5/27.5 A

Output: 3L/N/PE or 3L/PE, 220/380 Vac, 230/400 Vac, 240/415 Vac, 50/60 Hz, max 41.7 A, max 27.5 kVA

### GW30K-SDT-C30:

PV input: Max. 1100 Vdc, MPPT voltage range: 140-1000 Vdc, max: 42/32 A, Isc PV: 52.5/40 A

Output: 3L/N/PE or 3L/PE, 220/380 Vac, 230/400 Vac, 240/415 Vac, 50/60 Hz, max 50 A, max 33 kVA

--END--